

Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HD):** Conforms to ASTM A123 or A153 **Perma-**
- **Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (GD):** Conforms to ASTM B633, Type II SC1
- **Plain (BK):** No finish

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS4):** Conforms to ASTM A240 or A276, Type 304 *
- **Stainless Steel, Type 316 (SS6):** Conforms to ASTM A240 or A276, Type 316 *
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 *

Part No.	Finish	Product Weight / Piece (lbs)
PS 3164	HD	2.883
PS 3164	GR	2.72

Design Moment on Upright Channel:

- 16 Ga. Channel:** 6,500 in-lbs
- 14 Ga. Channel:** 9,100 in-lbs
- 12 Ga. Channel:** 13,000 in-lbs

