AS 808





## Materials & Finishes - Standard:

- Base Metal: Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
  Electrogalvanized (EG): Conforms to ASTM B633, Type III SC1
  Hot Dip Galvanized (HD): Conforms to ASTM A123 or A153 PermaGreen (GR): Conforms to commercial standards for powder coating
  Perma-Gold (GD): Conforms to ASTM B633, Type II SC1 Plain (BK): No finish

Materials & Finishes - Special Metals:

- Stainless Steel, Type 304 (SS4): Conforms to ASTM A240 or A276, Type 304 \*
- Stainless Steel, Type 316 (SS6): Conforms to ASTM A240 or A276, Type 316 \*
- Aluminum (AL): Conforms to ASTM B209, Type 1100F or 5052-H32 \*

Part No.	A	Finish	Product Weight / Piece (Ibs)
AS 808 6	6" (152.4)	HD	1.707
AS 808 06	6" (152.4)	GR	1.61
AS 808 6	6" (152.4)	SS4	1.61
AS 808 12	12" (304.8)	HD	2.767
AS 808 12	12" (304.8)	GR	2.61
AS 808 12	12" (304.8)	SS4	2.61
AS 808 18	18" (457.2)	HD	3.827
AS 808 18	18" (457.2)	GR	3.61
AS 808 18	18" (457.2)	SS4	3.61
AS 808 24	24" (609.6)	HD	4.887
AS 808 24	24" (609.6)	GR	4.61
AS 808 24	24" (609.6)	SS4	4.61