



FIG. 62 - Junior Top Beam Clamp

Material: Ductile iron with hardened steel set screw. 304 (62SS) and 316 (62SX) stainless steel.

Finish: Plain or electro-galvanized

Service: Designed to attach hanger rod to the top flange of a beam or bar joist where flange thickness does not exceed 5/8 of an inch.

Approvals: U.L. - U.L.C. listed 3/8 and 1/2 (1/2 for 4" IPS max). FM approved for 3/8 only. Complies with Federal Specification A-A-1192 A (Type# 19) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 19).

Ordering: Specify rod size, material, figure number and finish.

Notes: See MSS SP-69 for proper set screw recommendations. Stainless steel beam clamps are recommended for corrosive environments. **Order 62D for domestic**



ROD SIZE A	SET SCREW	B	C	D	E	F	MAX PIPE SIZE	MAX REC LOAD (lbs)	WGT EACH (lbs)
$\frac{3}{8}$ -16	$\frac{3}{8}$ -16	$1\frac{5}{16}$	$1\frac{1}{2}$	$\frac{1}{2}$	1	$\frac{7}{8}$	4	350	0.320
$\frac{1}{2}$ -13	$\frac{3}{8}$ -16	$1\frac{5}{16}$	$1\frac{1}{2}$	$\frac{1}{2}$	1	$\frac{7}{8}$	4	470	0.320
$\frac{5}{8}$ -11	$\frac{3}{8}$ -16	$1\frac{3}{4}$	$1\frac{3}{4}$	$\frac{5}{8}$	$1\frac{3}{8}$	$1\frac{1}{8}$	5	550	0.580
$\frac{3}{4}$ -10	$\frac{3}{8}$ -16	$1\frac{7}{8}$	$1\frac{7}{8}$	$\frac{5}{8}$	$1\frac{3}{8}$	$1\frac{3}{8}$	6	700	0.820
$\frac{7}{8}$ -9	$\frac{1}{2}$ -13	$2\frac{3}{8}$	$1\frac{7}{8}$	$\frac{5}{8}$	$1\frac{3}{8}$	$1\frac{3}{8}$	8	1000	0.795